

GEN-SET



GH 8000E-3



PORTABLE POWER



POWERED by
HONDA™

Technical Data

Model	GH 8000E
Type	Portable
Speed	3000 RPM
Frequency	50 Hz
Phases / Voltage	3/415
Max power kW	8 kW
Max Output kVA	9 kVA
Noise Level (dBA @ 7 m)	76
Frame	Extra Large Roll Frame
Electric Start	Battery carrier and leads

Engine

Manufacturer	Honda
Engine Model	iGX 440
Type	O.H.V.
Starting	Recoil & Electric start
Fuel	Unleaded petrol
Run Time	2.5 h
Consumption	2.1 L/h
Tank Capacity	6.5 L
Engine Protection	Low oil level
HP 3600 rpm max	15
Cubic Capacity	438 Cm ³
Oil Capacity	1.1 L

Alternator

Alternator Brand	Meccalte
Type	Brushless
Harmonic distortion	Less than 5%
protection class	IP 23
insulation class	Class H

Outlets

Outlet	20 amp 5 Pin Three Phase with C/B
--------	-----------------------------------

Dimensions and Weight

Length	84 Cm
Width	50 Cm
Height	57 Cm
Weight	80 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Long range Tank	15 Litre Capacity
Wheel kits	Two wheel or four wheel
Frames	Extra large Roll Frames
Battery	Wet Charged
Fuel	LPG Conversion
Control Systems	Auto start, 2 Wire remote, AMF, SMS
Alternators	Oversized, Single or Three Phase

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only