



GHW200-7E



## PORTABLE WELDER

POWERED by  
**HONDA**™



### Technical

|                               |                        |
|-------------------------------|------------------------|
| <b>Model</b>                  | GHW200/7E              |
| <b>Type</b>                   | Portable               |
| <b>Speed</b>                  | 3000 RPM               |
| <b>Phase/Voltage</b>          | 1/240                  |
| <b>Frequency</b>              | 50 Hz                  |
| <b>Welding Duty Cycle 35%</b> | 200 amp AC             |
| <b>Welding Duty Cycle 60%</b> | 180 amp AC             |
| <b>Strike Voltage</b>         | 75 V                   |
| <b>Output kVA / kW</b>        | 7.0 kVA / 5.6 kW       |
| <b>Noise Level (dBA @ 7m)</b> | 72                     |
| <b>Frame</b>                  | Extra Large roll frame |

### Engine

|                         |                            |
|-------------------------|----------------------------|
| <b>Manufacturer</b>     | Honda                      |
| <b>Engine Model</b>     | GX390                      |
| <b>Type</b>             | O.H.V.                     |
| <b>Starting</b>         | Recoil & Electric start    |
| <b>Fuel</b>             | Unleaded Petrol            |
| <b>Run Time</b>         | 2.6 hr @ 100%, 3.8hrs @60% |
| <b>Tank Capacity</b>    | 6.1 L                      |
| <b>HP 3000 rpm cont</b> | 8.0 HP                     |
| <b>Cubic Capacity</b>   | 389 Cm3                    |
| <b>Oil Capacity</b>     | 1.1 L                      |

### Alternator

|                            |              |
|----------------------------|--------------|
| <b>Alternator Brand</b>    | Sincro       |
| <b>Type</b>                | Brushless    |
| <b>Harmonic Distortion</b> | Less than 5% |
| <b>Protection Class</b>    | IP 23        |
| <b>Insulation Class</b>    | Class H      |

### Fittings

|               |  |
|---------------|--|
| <b>Outlet</b> | 10amp + 15amp switched with thermal overload   |
| <b>Leads</b>  | 5m Leads with Electrode Holder and Earth Clamp |

### Dimensions & Weight

|               |       |
|---------------|-------|
| <b>Length</b> | 85 Cm |
| <b>Width</b>  | 57 Cm |
| <b>Height</b> | 60 Cm |
| <b>Weight</b> | 80 Kg |

### Options

|                      |  |
|----------------------|--|
| <b>Outlets</b>       | Weather protected IP33 & Weatherproof IP66 |
| <b>Protection</b>    | RCD/ELCB IP30 or IP66                      |
| <b>Wheel kits</b>    | Two wheel or four wheel                    |
| <b>Frames</b>        | Extra large Roll Frames                    |
| <b>Welding Leads</b> | Leads made to measure                      |
| <b>Fuel Tank</b>     | 15 Litre Long Range Tank                   |