



Genelite

GK6.5



DIESEL POWER

Kubota




Technical

Model	GK6.5
Type	Open Set Skid
Speed	1500 RPM
Phase/Voltage	3/240-415
Frequency	50 Hz
Standby power kVA/kW	7kVA / 5.6kW
Continuous Output	6.5kVA / 5.2kW
Control Panel	Set mounted
Frame	Skid

Engine

Manufacturer	Kubota
Engine Model	D905
Type	Indirect
Starting	Electric start
Fuel	Diesel
Consumption	1.03 L/h @75%
Fuel Tank Capacity	Tank Offered as Option
HP 1500 rpm max	8.8 HP
Cubic Capacity	0.898 L
Oil Capacity	5.1 L

Alternator

Alternator Brand	Sincro, Meccalte
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Controls

Key Start	Key Start with Engine Protection for oil and water
Output Circuit Breaker	IP66 enclosed 3 pole circuit breaker

Dimensions & Weight

Length	1.5 Cm
Width	0.75 Cm
Height	1.1 Cm
Weight	320 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Controls	Remote Start, AMF
Weather Cover	Galvanised Basic
Fuel Tanks	Built To Requirement
Alternators	Oversized, Single or Three Phase