



GLDW200E

PORTABLE WELDER




Technical

Model	GLDW200E
Type	Portable
Speed	3000 RPM
Phase/Voltage	1/240
Frequency	50 Hz
Welding Duty Cycle 60%	200 amp AC
Strike Voltage	75 V
Output kVA / kW	7.0 kVA / 5.6 kW
Noise Level (dBA @ 7m)	82
Frame	Extra Large roll frame

Engine

Manufacturer	Lombardini
Engine Model	15LD440E
Starting	Electric start
Fuel	Diesel
Run Time	1.8 @75%
Tank Capacity	5.0 L
HP 3000 rpm cont	9.4 HP
Cubic Capacity	442 Cm3
Oil Capacity	1.5 L

Alternator

Alternator Brand	Sincro
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Fittings

Outlet	10amp + 15amp switched with thermal overload
Leads	5m Leads with Electrode Holder and Earth Clamp

Dimensions & Weight

Length	85 Cm
Width	57 Cm
Height	60 Cm
Weight	107 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Wheel kits	Two wheel or four wheel
Welding Leads	Leads made to measure