



GY15iW



DIESEL IRRIGATION POWER



Technical

Model	GY15iW
Type	Weather Cover
Speed	1500 RPM
Phase/Voltage	3/240-415
Frequency	50 Hz
Standby power kVA/kW	16.5kVA / 13.2kW
Continuous Output	15kVA / 12kVA
Control Panel	Set mounted
Frame	Skid Galvanised

Engine

Manufacturer	Yanmar
Engine Model	3TNV84T
Type	Direct
Starting	Electric start
Fuel	Diesel oil
Consumption	3.1 L/h @75%
Fuel Tank Capacity	Nil Offered as Option
kWm 1500 rpm	14
Cubic Capacity	1.496 L
Oil Capacity	6.7 L

Alternator

Alternator Brand	Sincro, Meccalte
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Control

Panel	Key Start Control with Engine Protection
Circuit Breaker	IP66 Enclosed

Dimensions & Weight

Length	1.5 Cm
Width	0.75 Cm
Height	1.1 Cm
Weight	550 Kg

Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	RCD/ELCB IP30 or IP66
Fuel Tanks	Built To Requirement