



## DEPENDABLE POWER

Super Series 05  
Kubota Diesel



Stamford Alternator



Deep Sea Controls



### Technical

Model	OZK10SA
Type	Heavy Duty
Speed	1500 RPM
Phase/Voltage	3, 240 / 415
Frequency	50 Hz
Stdby Power kVA/kW	11kVA / 8.8kW
Prime Output kVA / kW	10kVA / 8.0kW
Noise Level (dBA @ 7m)	60dB(A)
Fuel Capacity	24 Hrs 65 Litres

### Engine

Manufacturer	Kubota Diesel
Engine Model	D1105-BG
Type & Cylinder	4 Stoke – 3 L
Induction	Naturally Aspirated
Fuel Consumption	2.3L @ 100%, 1.9L @ 75%, 1.4L @ 50% Load
Coolant Capacity	5.0 L
Governor	Mechanical
Cubic Capacity	1.123 L
Oil Capacity	5.1 L

### Alternator

Alternator Brand / Model	Stamford / BC1164D – PI044H
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

### Canopy

Skid	Bunded fuel tank with fork lift pockets and skid tie down points
Canopy	Centre Lift, lockable doors with control panel viewing window
Paint Finish	Heavy duty powder coat finish white canopy with a black base
Emergency Stop	External Emergency Stop Fitted

### Dimensions & Weight

Length	1.64m
Width	0.76m
Height	1.135m
Weight	629 Kg

### Controls

Controller	Deep Sea 702 with Analogue Metering
Circuit Breaker	Two Pole RCD MCBO
Battery Isolator	Fitted with canopy adjacent battery

### Outlets

Outlets 3 Phase	1 x 20amp 5pin IP66 c/w RCD & C/B
Outlets 1 Phase	3 x 15amp 3pin IP66 c/w RCD & C/B
PMG Option	Available with PIO44H