



Genette



GC1000S

Model GC1000S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 1030kVA / 824 kW
Prime Output 1000kVA / 800 kW
Noise Level @ 7m 87dB(A)
Fuel Capacity 1450 L

Length 6.058m
Width 2.44m
Height 2.73m
Weight 12,475 kg

Engine

Manufacturer Cummins Diesel
Engine Model KTA38G5
Type & Cylinder 4 Stroke – V12
Induction Turbocharged After Cooled
Fuel Consumption
209 L @ 100%, 169 L @ 75%, 113 L @ 50% Load
Coolant Capacity 290 L
Governor Electronic
Cubic Capacity 38 L
Oil Capacity 135 L

Controls

Controller DeepSea DSE7420 with LCD Metering
Circuit Breaker Three Pole
Emergency Stop Included

Options

Synchronizing
Grid / Mains, Max Demand Lopping, Multiple Sets

Alternator

Alternator Brand / Model Stamford / LV634E
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H



East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912