



Genette

GC200S

Model GC200S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 212kVA / 169 kW
Prime Output 200kVA / 160 kW
Noise Level @ 7m 73 dB(A)
Fuel Capacity 1330 Litres

Length 3.592m
Width 1.342m
Height 2.16m
Weight 2960 kg

Engine

Manufacturer Cummins Diesel
Engine Model 6CTAA8.3G2
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged Air To Air After Cooled
Fuel Consumption
45 L @ 100%, 34L @ 75%, 23L @ 50% Load
Coolant Capacity 13 L
Governor Electronic
Cubic Capacity 8.3 L
Oil Capacity 23 L

Options

Outlets Single or 3 Phase Options
PMG Option

Controls

Controller DeepSea 7420 with LCD Metering
Circuit Breaker Four Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford / UCi274H
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop