



# Genette

## GC250S

**Model** GC250S  
**Speed** 1500 RPM  
**Phase/Voltage** 3, 415  
**Frequency** 50 Hz

**Stdby Power** 265kVA / 212 kW  
**Prime Output** 250kVA / 200 kW  
**Noise Level @ 7m** 74 dB(A)  
**Fuel Capacity** 1300 Litres

**Length** 3.66m  
**Width** 1.32m  
**Height** 2.26m  
**Weight** 3141 kg

### Engine

**Manufacturer** Cummins Diesel  
**Engine Model** 6LTAA8.9G2  
**Type & Cylinder** 4 Stroke – 6 L  
**Induction** Turbocharged Air To Air After Cooled  
**Fuel Consumption**  
53 L @ 100%, 39L @ 75%, 27L @ 50% Load  
**Coolant Capacity** 18 L  
**Governor** Electronic  
**Cubic Capacity** 8.9 L  
**Oil Capacity** 27 L

### Canopy

**Skid** Bunded fuel tank with fork lift pockets and skid tie down points  
**Canopy** Centre Lift, lockable doors with control panel viewing window  
**Path Finish** Heavy duty powder coat finish white canopy with a black base  
**Emergency Stop** External Emergency Stop Fitted

### Controls

**Controller** DeepSea 7420 with LCD Metering  
**Circuit Breaker** Four Pole  
**Battery Isolator** Fitted adjacent battery

### Alternator

**Alternator Brand / Model** Stamford / UCi274K  
**Type** Brushless  
**Harmonic Distortion** Less than 5%  
**Protection Class** IP 23  
**Insulation Class** Class H

### Options

**Synchronizing** Grid / Mains, Max Demand Lopping  
**Protection** RCD/ELCB IP30 or IP66  
**PMG** MX341 or MX321