



GC1250S

Model GC1250S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 1400kVA / 1120 kW
Prime Output 1250kVA / 1000 kW
Noise Level (dBA @ 7m) 87dB(A)
Fuel Capacity 1500 Litres

Length 6.058m
Width 2.44m
Height 2.73m
Weight 15,280 kg

Engine

Manufacturer Cummins Diesel
Engine Model KTA50G3
Type & Cylinder 4 Stroke – V16
Induction Turbocharged After Cooled
Fuel Consumption
261 L @ 100%, 199 L @ 75%, 139 L @ 50% Load
Coolant Capacity 351 L
Governor Electronic
Cubic Capacity 50 L
Oil Capacity 177 L

Container Set

20' Container
ISO Container HC, with integral muffler
Paint Finish
Heavy duty powder coat finish White
Emergency Stop External Emergency Stop Fitted

Controls

Controller DeepSea DSE7420 with LCD Metering
Circuit Breaker Three Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford / LVi634G
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Options

Synchronizing
Grid / Mains, Max Demand Lopping, Multiple Sets
Protection RCD/ELCB IP30 or IP66
PMG MX321

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912