



Genette

GC40S-1

Model GC40S
Speed 1500 RPM
Phase/Voltage 1, 240
Frequency 50 Hz

Stndby Power 44kVA / 35.2kW
Prime Output 40 kVA / 32kW
Noise Level @ 7m 67dB(A)
Fuel Capacity 270 Litres

Length 2.688m
Width 1.1m
Height 1.76m
Weight 1447 kg

Engine

Manufacturer Cummins Diesel
Engine Model 4BT3.9G1
Type & Cylinder 4 Stroke – 4 L
Induction Turbocharged
Fuel Consumption
9.4L @ 100%, 6.2L @ 75%, 4.5L @ 50% Load
Coolant Capacity 8 L
Governor Mechanical
Cubic Capacity 3.9 L
Oil Capacity 11 L

Options

Outlets 3 Phase Option
PMG EBS Option

Controls

Controller Remote Start with Analog Metering
Circuit Breaker Four Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford / UCi224E
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop