



Genette

GC500

Model GC500
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 575kVA / 460 kW
Prime Output 500kVA / 400 kW
Fuel Capacity 980 Litres

Length 3.87m
Width 1.37m
Height 2.17m
Weight 4408 kg

Engine

Manufacturer Cummins Diesel
Engine Model KTA19G4
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged After Cooled
Fuel Consumption
107 L @ 100%, 82 L @ 75%, 57 L @ 50% Load
Coolant Capacity 91 L
Governor Electronic
Cubic Capacity 19 L
Oil Capacity 50 L

Options

Synchronizing
Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG MX341 or MX321

Controls

Controller Auto Start with Analog Metering
Circuit Breaker Four Pole
Battery Isolator

Alternator

Alternator Brand / Model Stamford / HCi544D
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912