



Genette



GC500S

Model GC500S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 575kVA / 460kW
Prime Output 500kVA / 400 kW
Noise Level (dBA @ 7m) 77dB(A)
Fuel Capacity 1020 Litres

Length 4.51m
Width 1.55m
Height 2.56m
Weight 5937 kg

Engine

Manufacturer Cummins Diesel
Engine Model KTA19G4
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged After Cooled
Fuel Consumption
107 L @ 100%, 82 L @ 75%, 57 L @ 50% Load
Coolant Capacity 91 L
Governor Electronic
Cubic Capacity 19 L
Oil Capacity 50 L

Options

Synchronizing
Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG MX341 or MX321

Controls

Controller DeepSea DSE7420 with LCD Metering
Circuit Breaker Four Pole
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford / HCi544D
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912