



Genette

GC575

Model GC575
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Study Power 636kVA / 509 kW
Prime Output 575kVA / 460 kW
Fuel Capacity 940 Litres

Length 4.04m
Width 1.69m
Height 2.37m
Weight 4685 kg

Engine

Manufacturer Cummins Diesel
Engine Model KTA19G6
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged After Cooled
Fuel Consumption
127 L @ 100%, 92 L @ 75%, 64 L @ 50% Load
Coolant Capacity 91 L
Governor Electronic
Cubic Capacity 19 L
Oil Capacity 50 L

Options

Synchronizing
Grid /Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG MX341 or MX321

Controls

Controller Remote Start with Analog Metering
Circuit Breaker Four Pole
Battery Isolator

Alternator

Alternator Brand / Model Stamford / HCi544E
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912