



Genette

GC60S-1

Model GC60S
Speed 1500 RPM
Phase/Voltage 1, 240
Frequency 50 Hz

Stdby Power 66kVA / 52.8 kW
Prime Output 60kVA / 48kW
Noise Level (dBA @ 7m) 69 dB(A)
Fuel Capacity 360 Litres

Length 2.689m
Width 1.1m
Height 1.76m
Weight 1570 kg

Engine

Manufacturer Cummins Diesel
Engine Model 4BTA3.9G2
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged After Cooled
Fuel Consumption
13.1L @ 100%, 9.8L @ 75%, 6.7L @ 50% Load
Coolant Capacity 8 L
Governor Electronic
Cubic Capacity 3.9 L
Oil Capacity 11 L

Outlets

Outlets Single Phase
PMG MX341 or MX321

Controls

Controller DeepSea 7320 with LCD Metering
Circuit Breaker Four Pole
Emergency Stop Included

Alternator

Alternator Brand / Model Stamford / UCi274C
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bundled fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912