



Genette



GK15S

Model GK15S
Type Heavy Duty
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 16.5kVA / 13.2 kW
Prime Output 15kVA / 12.0 kW
Fuel Capacity 100 Litres

Length 2.04m
Width 1.12m
Height 1.35m
Weight 922kg

Engine

Manufacturer Kubota Diesel
Engine Model D1703-BG
Type & Cylinder 4 Stroke – 3 L
Induction Naturally Aspirated
Fuel Consumption
3.8L @ 100%, 3.0L @ 75%, 2.1L @ 50% Load
Coolant Capacity 5.0 L
Governor Mechanical
Cubic Capacity 1.67 L
Oil Capacity 7.0 L

Outlets

Outlets 3 Phase 1 x 20amp IP66 with CB
Outlets Single Phase
3 x 15amp IP66 with RCD MCBO
EBS PMG Option

Controls

Controller Remote Start with Analog Metering
Circuit Breaker Four Pole
Battery Isolator Fitted with canopy adjacent battery

Alternator

Alternator Brand / Model Stamford / Pi144E
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop