



Genelite

GP500

Model GP500
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Standby Power 550kVA / 440 kW
Prime Output 500kVA / 400 kW
Fuel Capacity 950 Litres

Length 3.765m
Width 1.17 m
Height 2.15 m
Weight 3820 kg

Engine

Manufacturer Perkins Diesel
Engine Model 2506C-E15TAG2
Type & Cylinder 4 Stroke – 6L
Induction Turbo Charged After Cooled
Fuel Consumption 99 L @ 100%,
73 L @ 75%, 51 L @ 50% Load
Coolant Capacity 39 L
Governor Electronic
Cubic Capacity 15 L
Oil Capacity 62 L

Controls

Controller Remote Start with LCD Metering
Circuit Breaker Four Pole
Battery Isolator

Options

Synchronizing Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG R450

Alternator

Alternator Brand / Model Leroy Somers LSA47.2M7
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912