



Genette

GP500S

Model GP500S
Type Heavy Duty
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Standby Power 550kVA / 440 kW
Prime Output 500kVA / 400 kW
Noise Level (dBA @ 7m) 75dB (A)
Fuel Capacity 1600 Litres

Length 4.58 m
Width 1.56 m
Height 2.55 m
Weight 5396 kg

Engine

Manufacturer Perkins Diesel
Engine Model 2506C-E15TAG2
Type & Cylinder 4 Stroke – 6 L
Induction Turbo Charged After Cooled
Fuel Consumption 106 L @ 100%,
85 L @ 75% Load, 55 L @ 50%
Coolant Capacity 39 L
Governor Electronic
Cubic Capacity 15 L
Oil Capacity 62 L

Alternator

Alternator Brand / Model Leroy Somers
LSA47.2M8
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Controls

Controller DeepSea 7420 with LCD Metering
Circuit Breaker Four Pole
Battery Isolator Fitted adjacent battery

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Paint Finish Heavy duty powder coat finish white canopy with black base
Emergency Stop External Emergency Stop Fitted

Options

Synchronizing Grid / Mains, Max Demand Lopping
Protection RCD/ELCB IP30 or IP66
PMG R450 &/or AREP

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912