



Genette

GP80S

Model GP80S
Type Heavy Duty
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Standby Power 88kVA / 70.4 kW
Prime Output 80kVA / 64 kW
Noise Level (dBA @ 7m) 73dB(A)
Fuel Capacity 550 Litres

Length 2.79 m
Width 1.15 m
Height 1.9 m
Weight 1852 kg

Engine

Manufacturer Perkins Diesel
Engine Model 1104A-44TG2
Type & Cylinder 4 Stroke – 4 L
Induction Turbo Charged
Fuel Consumption 18.7 L @ 100%,
14 L @ 75% , 9.7 L @ 50% Load
Coolant Capacity 13.2 L
Governor Mechanical
Cubic Capacity 4.4 L
Oil Capacity 8.3 L

Alternator

Alternator Brand / Model Leroy Somers
LSA44.2VS2
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Controls

Controller Remote Start with LCD Metering
Circuit Breaker Four Pole
Battery Isolator Fitted adjacent battery

Options

Outlets Single Phase Option
PMG R438

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre Lift, lockable doors with control panel viewing window
Paint Finish Heavy duty powder coat finish white canopy with black base
Emergency Stop External Emergency Stop

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Head Office Ph. 1300 305 912
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912