

Model OZGPC250S Speed 1500 RPM Phase/Voltage 3, 415 Frequency 50 Hz Power Factor .8 Stdby Power 275kVA / 220kW Prime Output 250kVA / 200kW Noise Level (dBA @ 7 m) 71.9dB(A) Fuel Run Time 24 Hours Length 3.5 m Width 1.08 m Height 2.12 m Weight 3121 kg

Engine

Manufacturer Cummins Diesel Engine Model 6CTAA8.9G2

Type & Cylinder 4 Stroke - 6 L

Induction Turbocharged After Cooled

Fuel Consumption 53 L @ 100%

39 L @ 75%, 29 L @ 50% Load

Coolant Capacity 18 L

Governor Electronic

Cubic Capacity 8.9 L

Oil Capacity 27 L

Warranty World Wide as per 3381307 Publication

Alternator

Alternator Brand / Model OEM AVR Controlled

Type Brushless

Harmonic Distortion Less than 3%

Protection Class IP 23

Insulation Class Class H

Controls

Controller SmartGen 6120 with LCD Display Circuit Breaker Moulded Case 3 Pole Battery Isolator Fitted with canopy adjacent battery

Canopy

Skid Base fuel tank with fork lift pockets and skid tie down points

Canopy Centre Lift, lockable doors with control panel viewing window

Paint Finish Heavy duty powder coat finish white canopy with a black base

Emergency Stop External Emergency Stop Fitted

Options

Outlets 1 x 32 AMP 3 Phase / 2 x 15 AMP Single Phase Weatherproof IP66