



Genelite

HP6700LN - 6.25kVA

Fuel Tank Capacity 14.5 L
Continous Running Time 7.5 hours @ 75% load
Gross Weight 158 kg (wet)

Dimensions (Package)

- Length 940 mm
- Width 540 mm
- Height 765 mm

Alternator

Rated Frequency 50 hz
Rated Output 4.8 kW
Max Output 5.0 kW
Rated Voltage 240 V
Power Factor 0.8 cos
Voltage Regulator AVR

Engine

Engine Model OEM Diesel
Type
- Single cylinder
- 4-stroke
- Air-cooled
- Diesel engine
Starting Fashion Electric Start

Part No: GID6700LN

HP6700LN - HP12000

The OzPower diesel portable generators are powered by an economical single cylinder diesel engine

Other features include

AVR controlled alternator
Thermal overload protection
Voltmeter
Power outlets 2 x 15amp 240 V
Long range integral fuel tank
Silenced weatherproof enclosure
Sealed battery
Centre lift

Optional Extras Available:

Automatic start
Automatic transfer switch
IP66 rated outlets 240 V (ELCB / RCD Protection)

East Coast Head Office Ph. 1300 305 912
Ph. +61 7 3277 8626 Fax. +61 7 3277 8627
24 Perrin Place, Salisbury QLD 4107

West Coast Office
Ph. +61 8 6305 0145 Fax. +61 8 6305 0219
2/6 Quantum Link, Wangara WA 6065

CALL US
1300 305 912