



Genette



GC175S

Model GC175S
Speed 1500 RPM
Phase/Voltage 3, 415
Frequency 50 Hz

Stdby Power 187kVA / 150kW
Prime Output 175kVA / 140kW
Noise Level 71.5dB(A)
Fuel Capacity 1200 Litres

Length 3.5m
Width 1.25m
Height 2.16m
Weight 2857kg

Engine

Manufacturer Cummins Diesel
Engine Model 6CTA8.3G2
Type & Cylinder 4 Stroke – 6 L
Induction Turbocharged After Cooled
Fuel Consumption
40 L @ 100%, 30L @ 75%, 20L @ 50% Load
Coolant Capacity 13 L
Governor Electronic
Cubic Capacity 8.3 L
Oil Capacity 23 L

Canopy

Skid Bunded fuel tank with fork lift pockets and skid tie down points
Canopy Centre lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop Fitted

Controls

Controller DeepSea 7420 with LCD Metering
Circuit Breaker Four Pole MCB
Battery Isolator Fitted adjacent battery

Alternator

Alternator Brand / Model Stamford / UCi274G
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Options

Outlets Single or 3 Phase Options
PMG MX341 or MX321