

Technical

Model CPS350-10

Type With or without trailer mount

Air Delivery 367CFM

Normal Effective 10.3bar(g) @ 150psi(g) **Working Pressure**

Engine

Manufacturer Cummins 4BTA3.9-C130 Type Starting Electric Start **Fuel** Diesel **Full Load RPM** 2300 RPM **Tank Capacity** 185 L Output Rating (kW/m) 97

Compressor

Direct Drive, Oil-Injected, Rotary Screw Type, Type Single Stage Compression, Water Cooled

Lube Oil Capacity 9 L

Controls

Control Panel Key Start with Engine Protection

Blow Off Valve Automatic on Shutdown

Box Unit Dimensions & Weight

	Trailer Mount	Without Trailer
Length	2862mm	2235mm
Width	1785mm	1300mm
Height	1833mm	1556mm
Weight (Wet)	2030kg	1680kg

Canopy

Steel Canopy Canopy **Noise Level** 77.9dB(A) @ 7m Spillage free frame Frame

Other Features

Trailer mounted version must be towed by a vehicle with a minimum 2 ton towing capacity or above. Towing

Compressor trailer fitted with ADR approved electric

override brakes.

Available with or without aftercooler **Options**

Quality air options, water separator and multiple

points of customisation available