



Ph 1300 305 912

www.genelite.com.au sales@genelite.com.au



People. Passion. Performance.



For Chicago Pneumatic, it isn't just about products. We value our endusers' and distributors' performance, and do our ultimate best to make it easy to work with us while providing reliable products with a passion.

- Broad product portfolio of robust compressors & tools
- Decades of experience & innovation
- 100% committed distributor partnership

This is how we keep you productive at all times, meeting the needs of professionals in vehicle service, general industry and construction around the globe.

People. Passion. Performance.



A differentiated offer matching your compressed air needs

Our piston portfolio covers a wide range of DIY and (semi-) professional needs, varying on technology, user comfort, and performance. Have a look at the matrix and define which range suits your needs best.

Technical characteristics

Occasional (plus)

1,5 - 3 hp

Air displ 180 - 340 l/min

Power size



Vessel size



Type name CPRA - CPRB

Applications

- Blowing
- Nailing & stapling
- Inflating
- Hobby painting
- Water spraying

Technology

Direct Driven

Intermittent use

Air displ

201 - 486 l/min

Power size

2 - 4 hp

10 bar

Vessel size

27 - 270 L

CPRC - CPRS

- Washing
- orbital sanding
- professional blowing
- professional screwing
- professional gravity painting
- impact and ratchet wrenchina

One Stage

Frequent use

Air displ. Power size

4 - 25 hp

Models up to 15 bar

514 - 2420 l/min

Vessel size

Up to 900 L

CPRD - CPRO - CPRS

 All professional service & repair

- Professional painting
- Bodv work

installations

- General torquing or wrenching.
- Dry air applications

Two Stage



SINGLE STAGE BELT DRIVE CPRC Series 1,5 - 3 kW / 2 - 4 hp







CPRC 3200 NS19S


Easy and performant

These belt driven units with a one stage compression are easy and efficient to handle, and they are powerful, performant and reliable at the same time. These units are available in stationary and moveable configurations, and the range includes silenced units for optimal user comfort.



Safe and robust

Metal beltguard offering sturdy protection.



Movability

Ergonomic and comfortable handling with rubber grips.



Lower air temperature

Large cooling fins aftercooler.



Simultaneous use

Dual outlets for more user flexibility.



User comfort

Easy maintenance and clear oil level indicators.





CPRC 290 NS12S





Ultimate user comfort

- 1 Blockable front wheels for most units
- 2 Different vessel sizes available
- 3 Double handle with rubber grip
- 4 Double outlet and user friendly pressure reducer
- 5 Strong reliable pumps

Technical Table		=		H		0		olt/ ase*		Vessel Capacity** (Liter)								
		l/ min	cfm	Нр	kW	Bar	230 /S	400 /T	втт	27L (M)	50L (M)	90L (M)	150L (M)	200L (M)	270L (M)	150L (F)	200L (F)	270L (F)
Ð	CPRC NS12	255	9,0	2,0	1,5	10												
€	CPRF NS12	255	9,0	2,0	1,5	10												
€	CPRC NS12S	255	9,0	2,0	1,5	10												
€	CPRC NS12S	320	11,3	3,0	2,2	10												
€	CPRC NS19S	393	13,9	3,0	2,2	10										(V)		
€	CPRC NS19S	486	17,2	4,0	3,0	10												

All models are DOL - Advanced models have pump with aftercooler

- * Volt/Phase: Single Phase 230V or Triphase 400V
- ** Vessel: M (Mobile on wheels) F (Fixed stationary) V (Vertical) BTT (Base mounted)
- Available configurations