



Genette



GKM15S-1

Model GKM15S-1
Type Medium Duty
Speed 1500 RPM
Phase/Voltage 1, 240
Frequency 50 Hz

Stdby Power 17kVA / 13kW
Prime Output 15kVA / 12kW
Noise Level @ 7m 61dBA
Fuel Capacity 37 Litres

Length 1.65m
Width 0.75m
Height 1.084m
Weight 712kg

Engine

Manufacturer Kubota Diesel
Engine Model D1703-BG
Type & Cylinder 4 Stroke – 3 L
Induction Naturally Aspirated
Fuel Consumption
4L @ 100%, 2.7L @ 75%
Coolant Capacity 7.1 L
Governor Mechanical
Cubic Capacity 1.67 L
Oil Capacity 7.6 L

Options

Outlets Single Phase
3 x 15amp IP66 with RCB MCBO
EBS PMG

Controls

Controller Remote Start with Analog Metering
Circuit Breaker Two Pole
Battery Isolator Fitted with canopy adjacent battery

Alternator

Alternator Brand / Model Mecc Alte ECP28 2L4A
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Canopy

Canopy Centre Lift, lockable doors with control panel viewing window
Path Finish Heavy duty powder coat finish white canopy with a black base
Emergency Stop External Emergency Stop