

GH12,000E-FBT



PORTABLE POWER



Technical

| Model | GH 12,000E-FBT |
|------------------------|---------------------------|
| Туре | Portable |
| Speed | 3000 RPM |
| Phase/Voltage | 1/240 |
| Frequency | 50 Hz |
| Max power kW | 10 kW |
| Continuous Output | 12.5 kVA |
| Noise Level (dBA @ 7m) | 74 |
| Frame | Skid Base with Roll Frame |

Engine

Manufacturer Engine Model Type Starting Fuel Run Time Tank Capacity HP 3000 rpm cont Cubic Capacity Oil Capacity Honda GX630 O.H.V. Electric start Unleaded Petrol 12 hrs @60% 50 L 14.1 HP 688 Cm3 1.9 L

Alternator

Alternator Brand Type Harmonic Distortion Protection Class Insulation Class Mecc Alte Brushless Less than 5% IP 23 Class H

Outlets

Outlet

2 x 15amp switched with thermal overload

Dimensions & WeightLength105 CmWidth55 CmHeight70 CmWeight155 Kg

Options

Outlets Protection Wheel kits Alternators Weather protected IP33 & Weatherproof IP66 RCD/ELCB IP30 or IP66 Four wheel Oversized, Single or Three Phase

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.