
GH2700H



GH2700H



PORTABLE POWER



Technical

Model Type Speed Phase/Voltage Frequency Max **Output @ 0.8pf** Noise Level (dBA @ 7m) Frame GH 2700H Hire Spec Portable 3000 RPM 1/240 50 Hz 2.7kVA 72 Small roll frame

Engine

Manufacturer Engine Model Type Starting Fuel Run Time Consumption Tank Capacity HP 3000 rpm Cont Cubic Capacity Oil Capacity Honda GX200 O.H.V. Recoil start Unleaded Petrol 2.7hrs @ 100%, 4hrs @ 60% Load 1.3 L/h 3.6 L 4.4 196 Cm3 0.6 L

Alternator

Alternator Brand Type Harmonic Distortion Protection Class Insulation Class Meccalte Brushless Less than 5% IP 23 Class H

Outlets

Outlet

2x 10amp switched with Circuit breakers & RCD Protected

Dimensions & Weight

Length Width	67 Cm 44 Cm
Height	48 Cm
Weight	39 Kg

Options

Long Range Tank

12 Litre Capacity

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.