




PORTABLE POWER




Technical

Model	GYD2000E – Mine Spec
Type	Portable
Speed	3000 RPM
Phase/Voltage	1/240
Frequency	50 Hz
Max power kW	2.0kW
Maximum Output	0.8PF
Noise Level (dBA @ 7m) Frame	80 Small Roll Frame

Engine

Manufacturer	Yanmar
Engine Model	L48 AE-DEG
Type	O.H.V.
Starting	Recoil & Electric Start
Fuel	Diesel
Run Time	3.12 hr @ 100%, 4.1hrs @75%
Tank Capacity	2.5 L
HP 3000 rpm cont	3.8 HP
Cubic Capacity	296 Cm3
Oil Capacity	1.1 L

Alternator

Alternator Brand	Mecc Alte
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Controls

Key Start	Engine protection oil pressure
Emergency Stop	Fitted

Mine Spec Inclusions

Lockable Isolators	Battery, Starter & Control Panel
RCD 30ma	Fitted to Outlets
Fire Extinguisher	1kg
Jump Start	Anderson Plug
Bunded Tray	Included
Centre Lift	Included
Earth Stake	Included
Outlets	10amp or 15amp IP66 C/B RCD

Dimensions & Weight

Length	67cm
Width	44cm
Height	48cm
Weight	54kg

Options

Wheel Kits	Two Wheel or Four Wheel
BMA Certification	Optional