GH12,000E-FBT/3



Technical

Model GH 12,000E-FBT/3

Type Portable
Speed 3000 RPM
Phase/Voltage 3/415
Frequency 50 Hz
Max power kW 10 kW
Continuous Output 12.5kVA
Noise Level (dBA @ 7m) 74

Frame Skid Base with Roll Frame

Engine

ManufacturerHondaEngine ModelGX630ETypeO.H.V.StartingElectric StartFuelUnleaded PetrolRun Time12 hrs @60%Tank Capacity50 l

Tank Capacity50 LHP 3000 rpm cont14.1 HPCubic Capacity688 cm³Oil Capacity1.9 L

Alternator

Alternator BrandMecc AlteTypeBrushlessHarmonic DistortionLess than 5%

Protection Class IP 23
Insulation Class Class H

Outlets

Outlets

 2×15 amp Single Phase with Thermal Overload

Protection

1 x 20amp 3 Phase with Thermal Overload

Protection

Dimensions & Weight

 Length
 105 cm

 Width
 55 cm

 Height
 70 cm

 Weight
 155 kg

Options

Outlets Weather protected IP33 & Weatherproof IP66

Protection RCD/ELCB IP30 or IP66

Wheel kits Four Wheel

Alternators Oversized, Single or Three Phase



