GH14,000E-FBT/3



Technical

Model GH 14,000E-FBT/3

Type Portable
Speed 3000 RPM
Phase/Voltage 3/415
Frequency 50 Hz
Max Output @ 0.8pf 11.5 kVA

Noise Level (dBA @ 74

7m) Frame Skid Base with Roll Over Frame

Engine

ManufacturerHondaEngine ModelGX690ETypeO.H.V.StartingElectric StartFuelUnleaded PetrolRun Time11 hrs @60%

 Tank Capacity
 50 L

 HP 3000 rpm cont
 14.1 HP

 Cubic Capacity
 688 cm³

 Oil Capacity
 1.9 L

Alternator

Alternator BrandMecc AlteTypeBrushlessHarmonic DistortionLess than 5%

Protection Class IP 23
Insulation Class Class H

Outlets

 2×15 amp Single Phase with Thermal Overload

Outlets Protection

1 x 20amp 3 Phase with Thermal Overload

Protection

Dimensions & Weight

 Length
 105 cm

 Width
 55 cm

 Height
 70 cm

 Weight
 150 kg

Options

Outlets Weather Protected IP33 & Weatherproof IP66

Protection RCD/ELCB IP30 or IP66

Wheel kits Four Wheel

Alternators Oversized, Single or Three Phase



