GH14,000E-LRT/3

PORTABLE POWER



Technical

Model GH14,000E-LRT/3

Type Portable
Speed 3000 RPM
Phase/Voltage 3/415
Frequency 50 Hz
Max Output @ 0.8pf 11.5 kVA
Noise Level (dBA @ 74

7m) Frame Extra Large Roll Frame

Engine

Manufacturer Honda GX690E **Engine Model** O.H.V. Type Electric Start Starting **Fuel** Unleaded Petrol **Run Time** 7hrs @60% **Tank Capacity** 25 L HP 3000 rpm continuous 14.1 HP **Cubic Capacity** 688 cm³ **Oil Capacity** 1.9 L

Alternator

Alternator Brand Mecc Alte

Type Brushless

Harmonic Distortion Less than 5%

Protection Class IP 23

Insulation Class Class H

Outlets

Outlets

 2×15 amp Single Phase with Thermal Overload

Protection

1 x 20amp 3 Phase with Thermal Overload

Protection

Dimensions & Weight

 Length
 86 cm

 Width
 57 cm

 Height
 60 cm

 Weight
 140 kg

Options

Outlets Weather protected IP33 & Weatherproof IP66

Protection RCD/ELCB IP30 or IP66

Wheel kits Four-Wheel

Frames Fuel Tank Base with Roll Over Frame
Alternators Oversized, Single or Three Phase



