



GH7000E-3



PORTABLE POWER

POWERED by  
**HONDA**™

**mecc alte spa**

### Technical

|                               |                        |
|-------------------------------|------------------------|
| <b>Model</b>                  | GH 7000E-3             |
| <b>Type</b>                   | Portable               |
| <b>Speed</b>                  | 3000 RPM               |
| <b>Phase/Voltage</b>          | 3/415                  |
| <b>Frequency</b>              | 50 Hz                  |
| <b>Max power kW</b>           | 7.0kW                  |
| <b>Continuous Output</b>      | 8.0kVA                 |
| <b>Noise Level (dBA @ 7m)</b> | 72                     |
| <b>Frame</b>                  | Extra Large Roll Frame |

### Engine

|                         |                            |
|-------------------------|----------------------------|
| <b>Manufacturer</b>     | Honda                      |
| <b>Engine Model</b>     | GX390E                     |
| <b>Type</b>             | O.H.V.                     |
| <b>Starting</b>         | Recoil & Electric Start    |
| <b>Fuel</b>             | Unleaded Petrol            |
| <b>Run Time</b>         | 2.6 hr @ 100%, 3.8hrs @60% |
| <b>Tank Capacity</b>    | 6.1 L                      |
| <b>HP 3000 rpm cont</b> | 8.0 HP                     |
| <b>Cubic Capacity</b>   | 389 cm <sup>3</sup>        |
| <b>Oil Capacity</b>     | 1.1 L                      |

### Alternator

|                            |              |
|----------------------------|--------------|
| <b>Alternator Brand</b>    | Mecc Alte    |
| <b>Type</b>                | Brushless    |
| <b>Harmonic Distortion</b> | Less than 5% |
| <b>Protection Class</b>    | IP 23        |
| <b>Insulation Class</b>    | Class H      |

### Outlets

|                |  |
|----------------|--|
| <b>Outlets</b> | 1 x 10amp 5 Pin IP66 3 Phase with Thermal Overload Protection<br>2 x 15amp 3 Pin Single Phase with Thermal Overload Protection |
|----------------|--|

### Dimensions & Weight

|               |       |
|---------------|-------|
| <b>Length</b> | 85 cm |
| <b>Width</b>  | 57 cm |
| <b>Height</b> | 60 cm |
| <b>Weight</b> | 80 kg |

### Options

|                        |  |
|------------------------|--|
| <b>Outlets</b>         | Weather protected IP33 & Weatherproof IP66 |
| <b>Protection</b>      | RCD/ELCB IP30 or IP66                      |
| <b>Wheel kits</b>      | Two Wheel or Four Wheel                    |
| <b>Frames</b>          | Extra Large Roll Frames                    |
| <b>Alternators</b>     | Oversized, Single or Three Phase           |
| <b>Long Range Tank</b> | 15 Litre Capacity                          |