GYD3500E



GYD3500E



PORTABLE POWER





Technical

Model
Туре
Speed
Phase/Voltage
Frequency
Max power kW @ 0.8pf
Continuous Output
Noise Level (dBA @ 7m)
Frame

GYD3500F Portable 3000 RPM 1/240 50 Hz 3.5kW 4.5kVA 80 Large roll frame

Engine

Manufacturer **Engine Model** Туре Starting Fuel Run Time Tank Capacity HP 3000 rpm cont **Cubic Capacity Oil Capacity**

Yanmar L70 AE-DEG O.H.V. Hand & Electric Start Diesel 2.9 hr @ 100%, 3.8hrs @75% 3.5 L 5.5 HP 296 Cm3 1.1 L

Alternator

Alternator Brand Туре **Harmonic Distortion Protection Class Insulation Class**

Meccalte Brushless Less than 5% IP 23 Class H

Outlets	
Outlet	10amp + 15amp switched with thermal overload
Dimensions & Weight	
Length	76 Cm

Width	50 Cm
Height	57 Cm
Weight	75 Kg

Options

Outlets Protection Wheel kits Alternators Weather protected IP33 & Weatherproof IP66 RCD/ELCB IP30 or IP66 Two wheel or four wheel Oversized, Single or Three Phase

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.